Series DC(S)

Features

· Small size but large capacity

· 70 1000hr


Applications

 memory back-up for Video, Audio, Cameras, Camcorder, Telephones, Printer, Car stereo, Computer, Notebook PC, Rice cooker etc



Specifications							
Items	Characteristics						
Operating temperature	-25 to +70						
Rated working voltage	5.5VDC						
Maximum surge voltage	6.3VDC						
Nominal Cap. range	0.22 to 0.47F						
Capacitance tolerance	-20% to +80%(at 25)						
Low temperature(-25) characteristics	Capacitance change : 50% of initial measured value at +25						
	Internal resistance : 300% times of initial specified value at +25						
Endurance	Capacitance change : ±30% of initial measured value						
	Internal resistance: 400% times of initial specified value						
	(After 1000hours application of rated DC working voltage at +70 ,						
	the capacitor shall meet the following limits.)						
Shelf life	After 1000hours storage at +70 without load, the capacitor shall						
	meet the specified limit for "Life"						

Dimensions in mm(not to scale)



Dimensions in mm(not to scale)

Part number	Operation	Capacitance	ESR	V type(mm)			H type(mm)		
Faithumber	Voltage (V)	(F)	(,@1kHz)	D	Н	Р	D	Н	Р
SCDCS5R5224	5.5	0.22	75	11.5	18	5	11.5	10.5	10
SCDCS5R5334		0.33	75	11.5	18	5	11.5	10.5	10
SCDCS5R5474		0.47	75	11.5	18	5	11.5	10.5	10