Series DM

Features

- · Small size but large capacity
- -70 1000hr

Applications


- Memory back-up for Cellular phone, Digital camera, PDA



Specifications

Items	Characteristics		
Operating temperature	-25 to +70		
Rated working voltage	2.5, 3.3VDC		
Nominal Cap. range	0.06 to 0.33F		
Capacitance tolerance	-20% to +80%(at 25)		
Low temperature(-25) characteristics	Capacitance change: 50% of initial measured value at +25		
	Internal resistance: 300% times of initial specified value at +25		
Endurance	Capacitance change: ±30% of initial measured value		
	Internal resistance: 400% times of initial specified value		
	(After 1000hours application of rated DC working voltage at +70 ,the		
	capacitor shall meet the following limits.)		
Shelf life	After 1000hours storage at +70 without load, the capacitor shall		
	meet the specified limit for "Life"		

Dimensions in mm(not to scale)



Dimensions in mm(not to scale)

Billionologia il minimot to coulo)					
Part number	Operating Voltage (V)	Capacitance (F)	ESR (, @1kHz)	D×L (mm)	
SCDM2R5473	2.5	0.047	500	4.8×1.4	
SCDM2R5204		0.2	100	6.8×1.4	
SCDM2R5334		0.33	100	6.8×2.1	
SCDM3R3473	3.3	0.047	1000	4.8×1.4	
SCDM3R3204		0.2	200	6.8×1.4	
SCDM3R3224		0.22	200	6.8×2.1	